

View Online at <https://aerobasegroup.com/nsn/5305-01-078-7242>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.600 inches and 0.693 inches

Fastener Length:

Between 0.719 inches and 0.750 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.233 inches and 0.279 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 8740

Screw Material Specification:

Mil-s-6050 military specification single material response or ams6300 assn standard single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification all treatment responses

Color:

Black

Thread Series Designator:

Unjc

Specification Data:

80205-nas514 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.