NSN 5305-01-079-1371

Thread Class:

Thread Direction:

За

N/a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-079-1371

Right-hand						
Thread Length:						
Between 0.251 inches and 0.301 inches						
Fastener Length:						
Between 0.823 inches and 0.853 inches						
Head Style:						
Pan						
Head Diameter:						
Between 0.357 inches and 0.373 inches						
Head Height:						
Between 0.122 inches and 0.133 inches						
Grip Diameter:						
Between 0.1885 inches and 0.1895 inches						
Internal Drive Style:						
Offset cruciform (torque set)						
Thread Diameter:						
0.190 inches						
Grip Length:						
Between 0.552 inches and 0.572 inches						
Thready Qty Per Inch (tpi):						
Thready Qty Per Inch (tpi): 32						
32						
32 Min. Tensile Strength (psi):						
32 Min. Tensile Strength (psi): 160000 pounds per square inch						
32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish:						
32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:						
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf						

NSN 5305-01-079-1371

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0