

View Online at <https://aerobasegroup.com/nsn/5305-01-079-2466>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.443 inches and 0.510 inches

**Fastener Length:**

Between 1.077 inches and 1.124 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.497 inches and 0.507 inches

**Grip Diameter:**

Between 0.2483 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.066 inches first hole and 0.086 inches first hole

**Single Shear Strength:**

4650 pounds per square inch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.614 inches and 0.634 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.926 inches first hole and 0.946 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas334 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0