NSN 5305-01-079-5136



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-079-5136 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.484 inches **Fastener Length:** Between 2.141 inches and 2.188 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Mil-s-8695 military specification 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-079-5136

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-8695 spec.