## NSN 5305-01-079-5137

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-079-5137 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.216 inches and 0.369 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.462 inches and 0.507 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 1010 **Screw Material Specification:** Qq-s-671 federal specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1 cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 2s style **Departure From Cited Document:** As modified by material and surface treatment Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-079-5137

Machine Screw - Page 2 of 2



Fiig:

A500d0