

View Online at <https://aerobasegroup.com/nsn/5305-01-079-5158>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.443 inches and 0.510 inches

Fastener Length:

Between 2.077 inches and 2.124 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.497 inches and 0.507 inches

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.066 inches first hole and 0.086 inches first hole

Single Shear Strength:

4650 pounds per square inch

Internal Drive Style:

Cross recess type ii

Thread Diameter:

0.250 inches

Grip Length:

Between 1.614 inches and 1.634 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.926 inches first hole and 1.946 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas334 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0