

View Online at <https://aerobasegroup.com/nsn/5305-01-079-6567>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.398 inches and 0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Fillister

Head Diameter:

Between 0.389 inches and 0.414 inches

Head Height:

Between 0.161 inches and 0.170 inches

Hole Diameter:

0.062 inches

Locking Feature:

Pellet threads

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

60000 pounds per square inch

Hole Configuration Style:

Round

Material:

Steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145 or steel comp 1146 or steel comp 1151 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 12114

Material Specification:

Qq-s-637 federal specification all material responses or 66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0