NSN 5305-01-079-6567

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-079-6567

| View Online at https://aerobasegroup.com/nsn/5305-01-079-6567 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.398 inches and 0.500 inches |
| Fastener Length: |
| Between 0.469 inches and 0.500 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.389 inches and 0.414 inches |
| Head Height: |
| Between 0.161 inches and 0.170 inches |
| Hole Diameter: |
| 0.062 inches |
| Locking Feature: |
| Pellet threads |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.250 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 60000 pounds per square inch |
| Hole Configuration Style: |
| Round |
| Material: |
| Steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 |
| or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145 or steel comp |
| 1146 or steel comp 1151 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 12114 |
| Material Specification: |
| Qq-s-637 federal specification all material responses or 66 federal standard all material responses |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Og-n-416 type 2 cl 3 federal specification single treatment response |

Unf

Thread Series Designator:

NSN 5305-01-079-6567

Socket Head Cap Screw - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0