NSN 5305-01-079-6567

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-079-6567

View Online at https://aerobasegroup.com/nsn/5305-01-079-6567
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.398 inches and 0.500 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Fillister
Head Diameter:
Between 0.389 inches and 0.414 inches
Head Height:
Between 0.161 inches and 0.170 inches
Hole Diameter:
0.062 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
60000 pounds per square inch
Hole Configuration Style:
Round
Material:
Steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132
or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145 or steel comp
1146 or steel comp 1151 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 12114
Material Specification:
Qq-s-637 federal specification all material responses or 66 federal standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Og-n-416 type 2 cl 3 federal specification single treatment response

Unf

Thread Series Designator:

NSN 5305-01-079-6567

Socket Head Cap Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0