NSN 5305-01-079-7248

Setscrew - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Thread Length:** Between 0.590 inches and 0.625 inches Fastener Length: Between 0.590 inches and 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches Hole Diameter: Between 0.165 inches and 0.180 inches **Point Length:** 0.090 inches **Point Style:** Oval **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity:** 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Hole Configuration Style: Round **Product Name:** Navy special project Material: Steel comp 1010 **Material Specification:** Qq-s-637 federal specification single material response **Surface Treatment:** Cadmium

NSN 5305-01-079-7248

Setscrew - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, ty1, cl2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0