NSN 5305-01-079-9582

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-079-9582 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 2.281 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.365 inches **Head Height:** Between 0.109 inches and 0.141 inches **Spline Major Diameter:** 0.365 inches Spline Width: 0.060 inches **First Diameter From Head:** 0.180 inches **Second Diameter From Head:** Between 0.1890 inches and 0.1895 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.500 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.875 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 304 or stainless steel **Material Specification:** Qq-s-763 type 302 cond b federal specification 1st material response or qq-s-763 type 304 cond b federal specification 2nd material response or ams 5378 assn standard 3rd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-079-9582

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0