NSN 5305-01-080-0666

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-080-0666 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.214 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.065 inches and 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.245 inches and 0.255 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 300 series federal specification single material response or 66 300 series federal standard single material response or comp 16-18 or 18-8 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response or def 130 fscm k0656 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-080-0666

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0