NSN 5305-01-080-4494

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-080-4494 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.375 inches **Fastener Length:** 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.141 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel bearing surface of head **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Zinc fastener and chromate fastener **Surface Treatment Specification:** Astm b633, type 2, class fe/zm 5 assn standard all treatment responses fastener **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-080-4494

Socket Head Cap Screw - Page 2 of 2



	- : -	~	NA	
UI	nit	UΤ	Measure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.