NSN 5305-01-080-4951

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-080-4951 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.165 inches and 0.175 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.177 inches and 0.225 inches First Diameter From Head: Between 0.080 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.156 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** With strip type locking element Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 430 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-080-4951

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0