NSN 5305-01-080-5714

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-080-5714 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.620 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** 0.092 inches **First Diameter From Head:** Between 0.095 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.370 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or astma582 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-080-5714

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0