

View Online at <https://aerobasegroup.com/nsn/5305-01-080-6608>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.159 inches and 1.219 inches

Fastener Length:

Between 2.486 inches and 2.516 inches

Head Style:

Hexagon

Head Height:

Between 0.390 inches and 0.422 inches

Width Between Flats:

Between 1.053 inches and 1.064 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

140000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.177 inches first hole and 2.197 inches first hole

Product Name:

Navy special project

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1012 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0