NSN 5305-01-080-9190

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-080-9190

| Thread Class: |
|---------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.306 inches and 0.356 inches |
| Fastener Length: |
| Between 0.754 inches and 0.784 inches |
| Head Style: |
| Fillister countersunk |
| Head Diameter: |
| Between 0.2966 inches and 0.3016 inches |
| Head Height: |
| 0.013 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches grip |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-080-9190

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

