## NSN 5305-01-081-0465

Setscrew - Page 1 of 2

Between 0.473 inches and 0.610 inches

Between 1.078 inches and 1.125 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

2a



View Online at https://aerobasegroup.com/nsn/5305-01-081-0465

Hea	ad Style:
Hex	xagon extended washer
Hea	ad Height:
Bet	ween 0.120 inches and 0.136 inches
Wic	dth Between Flats:
Bet	ween 0.244 inches and 0.250 inches
Ext	tended Washer Diameter:
Bet	ween 0.358 inches and 0.380 inches
Ext	tended Washer Thickness:
Bet	ween 0.019 inches and 0.031 inches
Poi	int Length:
Bet	ween 0.110 inches and 0.130 inches
Poi	int Diameter:
Bet	ween 0.115 inches and 0.120 inches
Poi	int Style:
Dog	g
Inte	ernal Drive Style:
W/c	o internal drive
Thr	read Diameter:
0.1	64 inches
Thr	ready Qty Per Inch (tpi):
32	
Hai	rdness Rating:
23.	0 rockwell c and 30.0 rockwell c
Spe	ecial Features:
Fur	nished with dupontzytel 70g13hsli nylon bushing
Ma	terial:
Ste	el comp 1022
Ma	terial Specification:
	e assn standard single material response
Sui	rface Treatment:
Cad	dmium
Sui	rface Treatment Specification:
G-4	4341-m code 15 fscm 16764 mfr ref single treatment response

## NSN 5305-01-081-0465

Setscrew - Page 2 of 2



Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A003b0