NSN 5305-01-081-2412

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-081-2412 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.375 inches **Head Style:** Round wedge **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Special Features:** Critical item hydrogen embrittlement relief required Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:**

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

NSN 5305-01-081-2412

Socket Head Cap Screw - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0