Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-081-2417

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
0.625 inches
Head Style:
Undercut pan no. 2
Head Diameter:
Between 0.347 inches and 0.361 inches
Head Height:
Between 0.091 inches and 0.101 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.125 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Zinc
Surface Treatment Specification:
Qq-z-325, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

NSN 5305-01-081-2417

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

