NSN 5305-01-081-2430



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-081-2430 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.120 inches **Fastener Length:** 2.000 inches **Head Style:** Fillister **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:**

0.312 inches

Width Across Flats:

0.250 inches

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

Special Features:

Critical item hydrogen embrittlement relief required

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unc

NSN 5305-01-081-2430

Socket Head Cap Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0