## NSN 5305-01-081-2457

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-081-2457 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.380 inches **Fastener Length:** 3.000 inches **Head Style:** Fillister **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** Between 0.430 inches and 0.438 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.438 inches Width Across Flats: 0.375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-01-081-2457

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0