

View Online at <https://aerobasegroup.com/nsn/5305-01-081-3102>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.372 inches and 0.422 inches

Fastener Length:

Between 0.570 inches and 0.600 inches

Head Style:

Fillister countersunk

Head Diameter:

Between 0.389 inches and 0.3948 inches

Head Height:

0.015 inches

Shoulder Diameter:

0.2646 inches first shoulder and 0.2651 inches first shoulder

Shoulder Length:

0.135 inches first shoulder

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Special Features:

Socket drive recess in thread end 0.095 in. Min 0.097 in. Maximum width across flats

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0