NSN 5305-01-081-3103

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-081-3103

| Thread Class: |
|--------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.372 inches and 0.422 inches |
| Fastener Length: |
| Between 1.007 inches and 1.037 inches |
| Head Style: |
| Fillister countersunk |
| Head Diameter: |
| Between 0.3898 inches and 0.3948 inches |
| Head Height: |
| 0.015 inches |
| Shoulder Diameter: |
| 0.2646 inches first shoulder and 0.2651 inches first shoulder |
| Shoulder Length: |
| 0.572 inches first shoulder |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| Socket drive recess in thread end 0.095 in. Min 0.097 in. Maximum width across flats |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |

Unjf

NSN 5305-01-081-3103

Shoulder Screw - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0