

View Online at <https://aerobasegroup.com/nsn/5305-01-081-4658>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.649 inches and 0.750 inches

Fastener Length:

Between 0.720 inches and 0.750 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Locking Feature:

Pellet threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.1875 inches and 0.1900 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

Color:

Black fastener

Material:

Steel fastener

Material Specification:

Mil-h-6875 military specification single material response

Surface Treatment:

Oxide fastener

Surface Treatment Specification:

Mil-c-13924, class 3 military specification single treatment response fastener

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-h-6875 spec.