

View Online at <https://aerobasegroup.com/nsn/5305-01-081-4658>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.649 inches and 0.750 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.365 inches and 0.375 inches

**Head Height:**

Between 0.244 inches and 0.250 inches

**Locking Feature:**

Pellet threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.1875 inches and 0.1900 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

150000 pounds per square inch

**Color:**

Black fastener

**Material:**

Steel fastener

**Material Specification:**

Mil-h-6875 military specification single material response

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924, class 3 military specification single treatment response fastener

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-h-6875 spec.