
# NSN 5305-01-081-4659

Setscrew - Page 1 of 2





### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 1.444 inches and 1.464 inches

### Fastener Length:

1.630 inches

Head Style:

Hexagon

Head Height:

Between 0.230 inches and 0.270 inches

### Width Between Flats:

Between 0.493 inches and 0.507 inches

### **Point Length:**

Between 0.166 inches and 0.186 inches

### **Point Diameter:**

Between 0.257 inches and 0.267 inches

Point Style:

Ball

**Internal Drive Style:** 

W/o internal drive

# Thread Diameter:

0.312 inches

# Thready Qty Per Inch (tpi):

24

# Hardness Rating:

40.0 rockwell c and 45.0 rockwell c

## Material:

Steel comp 4130

#### **Material Specification:**

Mil-s-6758, cond f4 military specification single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

# **Thread Series Designator:**

Unf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5305-01-081-4659

Setscrew - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.

