

View Online at <https://aerobasegroup.com/nsn/5305-01-081-6101>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.228 inches and 0.290 inches

Fastener Length:

Between 0.290 inches and 0.310 inches

Head Style:

Round

Head Diameter:

Between 0.287 inches and 0.309 inches

Head Height:

Between 0.107 inches and 0.120 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Primary Washer Outside Diameter:

Between 0.327 inches and 0.338 inches

Primary Washer Style:

Flat internal teeth

Primary Washer Material Thickness:

Between 0.018 inches and 0.023 inches

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

Sae j429 assn standard all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Bw-101b-p, fscm 06853 mfr ref 1st treatment response or bw-162a-p, fscm 06853 mfr ref 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A003b0