## NSN 5305-01-081-7368

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-081-7368

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 1.380 inches  |
| Fastener Length:  |
| 2.250 inches  |
| Head Style:   |
| Fillister   |
| Head Diameter:  |
| Between 0.642 inches and 0.656 inches                                     |
| Head Height:  |
| Between 0.430 inches and 0.438 inches                                     |
| Locking Feature:  |
| Patch threads   |
| Internal Drive Style:   |
| Hexagon   |
| Thread Diameter:  |
| 0.438 inches  |
| Width Across Flats:   |
| 0.375 inches  |
| Thready Qty Per Inch (tpi):   |
| 14  |
| Min. Tensile Strength (psi):  |
| 170000 pounds per square inch   |
| Hardness Rating:  |
| 38.0 rockwell c and 45.0 rockwell c                                       |
| Minimum Yield Strength:   |
| 150000 pounds per square inch   |
| Special Features:   |
| Critical item hydrogen embrittlement relief required                      |
| Material:   |
| Steel   |
| Material Specification:   |
| 66 federal standard single material response                              |
| Surface Treatment:  |
| Zinc  |
| Surface Treatment Specification:  |
| Qq-z-325, type 2, class 3 federal specification single treatment response |
| Thread Series Designator:   |
| Unc   |

## NSN 5305-01-081-7368

Socket Head Cap Screw - Page 2 of 2



| _  |    |    |     |      |  |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: |  |
| J. | 16 |    |     | HE.  |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0