NSN 5305-01-081-8910

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-081-8910

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
1.874 inches
Head Style:
Knurled no. 1
Head Diameter:
0.750 inches
Head Height:
0.438 inches
First Diameter From Head:
0.281 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
1.249 inches
Internal Drive Style:
Slot
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
16
Criticality Code Justification:
Zzzy
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 416
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Special Test Features:
Special quality control testing
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Unc

Thread Series Designator:

NSN 5305-01-081-8910

Externally Relieved Body Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0