
NSN 5305-01-081-9472

Close Tolerance Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.251 inches and 0.301 inches Fastener Length: Between 1.386 inches and 1.416 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1133 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-081-9472

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0