NSN 5305-01-082-0144

Thread Class:

Thread Direction:

За

N/a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-082-0144

Right-hand							
rught hand							
Thread Length:							
Between 0.291 inches and 0.341 inches							
Fastener Length:							
Between 0.613 inches and 0.643 inches							
Head Style:							
Pan							
Head Diameter:							
Between 0.473 inches and 0.492 inches							
Head Height:							
Between 0.162 inches and 0.175 inches							
Grip Diameter:							
Between 0.2485 inches and 0.2495 inches							
Internal Drive Style:							
Offset cruciform (torque set)							
Thread Diameter:							
0.250 inches							
Grip Length:							
Between 0.302 inches and 0.322 inches							
Thready Qty Per Inch (tpi):							
Thready Qty Per Inch (tpi):							
Thready Qty Per Inch (tpi): 28							
28							
28 Min. Tensile Strength (psi):							
28 Min. Tensile Strength (psi): 160000 pounds per square inch							
28 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish:							
28 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material:							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment:							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:							
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf							

NSN 5305-01-082-0144

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0