NSN 5305-01-082-0147

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-082-0147

3aFhread Direction:Right-handFhread Length:Between 0.251 inches and 0.301 inchesFastener Length:Between 0.573 inches and 0.603 inchesHead Style:PanHead Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesGrip Diameter:Offset cruciform (torque set)Internal Drive Style:0.164 inchesGrip Length:
Right-handThread Length:Between 0.251 inches and 0.301 inchesFastener Length:Between 0.573 inches and 0.603 inchesHead Style:PanHead Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inches
Thread Length:Between 0.251 inches and 0.301 inchesFastener Length:Between 0.573 inches and 0.603 inchesHead Style:PanHead Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inches
Between 0.251 inches and 0.301 inches Fastener Length: Between 0.573 inches and 0.603 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.322 inches Grip Diameter: Between 0.1625 inches and 0.115 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Fastener Length:Between 0.573 inches and 0.603 inchesHead Style:PanHead Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inches
Between 0.573 inches and 0.603 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.125 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Head Style:PanHead Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inches
Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Head Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesGrip Diameter:Between 0.1625 inches and 0.1635 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.164 inches
Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Head Height: Between 0.105 inches and 0.115 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Between 0.105 inches and 0.115 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Between 0.1625 inches and 0.1635 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.164 inches
Offset cruciform (torque set) Thread Diameter: 0.164 inches
Thread Diameter: 0.164 inches
0.164 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1132 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-082-0147

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

