Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-082-1374

Interact Direction:         Right-hand         Thread Length:         0.188 inches         Fastonr Length:         0.188 inches         Fastonr Length:         Between 0.409 inches and 0.440 inches         Head Sile:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.267 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thread State         Betweel Style:         Statinless steel         Statinless steel         Statinless steel         Statinless steel         Statiless steel         Statiless steel         Statiless steel         Statiless steel         Statiless steel         Statiless steel         Ditt Of Measure:         Na <th></th>	
Firead Direction:         Right-hand         Tread Length:         0.188 inches         Fastenr Length:         Between 0.409 inches and 0.440 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.087 inches and 0.097 inches         Forst Diameter From Head:         Between 0.087 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thread Vity Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Marcial:         Stainless steel         Surface Treatment:         Passivate         Marcial Constanter:         Vita Of Measure:         Vita Of Measure:         Vita Of Measure:         Passivate <th>Thread Class:</th>	Thread Class:
Right-Mad         Thread Length:         0.188 inches         Fastener Length:         Between 0.409 inches and 0.440 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         D.1252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Pelieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Series Designator:         Unic         Na         Unit Of Measure:            Dimilitarization:	
Tread Length:         0.188 inches         Fastener Length:         Between 0.409 inches and 0.440 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Diameter:         0.138 inches         Thread Style:         Staniels         Stareally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Pasivate         Thread Steines Designator:         Inc         Via         Materiat:         Stainless steel         Surface Treatment:         Pasivate         Thread Style:         Interd Style: </th <th></th>	
0.188 inches         Fastener Length:         Between 0.409 inches and 0.440 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thread y Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Steise Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No	
Fastener Length:         Between 0.409 inches and 0.440 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Heigh:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Stels Designator:         Unc         Sheft Life:         Na         Material:         Passivate         Thread Stels Designator:         Unc         Sheft Life:         Na         Dit Of Measure:         -         Na         Distance:         Na         Distance:     <	
Between 0.40 inches and 0.440 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Stainless steel         Stariace Treatment:         Passivate         Intread Stries Designator:         Inci         Na         Staff Life:         Na         Int of Measure:         Image:         Int of Measure:         Image:         Image:         Image:         Image:         Image:         Image:         Image:         Image:	
Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Na         Inter Offerst Designator:         Inc         Passivate         Inter Offerst Designator:         Inc         Na         Into ff Measure:         Into ff Measure:         Into ff Measure:         Image:         Image:         Image:         Image:         Image:         Image:         Image:         Image: <td< th=""><th>-</th></td<>	-
Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Incel Life:         Na         Inter Life:         Na         Inter Complement         Inter Compl	
Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Series Designator:         Inc         Na         Internal Cf Measure:         Na         Passivate         Dirticf Measure:         Na         Passivate         Dirticf Measure:         Na         Particif Passivate	
Between 0.256 inches and 0.270 inches         Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Series Designator:         Inc         Na         Dist Of Measure:         Init Of Measure:         Image:	
Head Height:         Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Series Designator:         Inc         Material:         Passivate         Thread Series Designator:         Inc         Material:         Inter Series Designator:         Inc         Material:         Passivate         Dirticf Measure:         Inter         Inter         Inter         Inter         Inti of Measure:         Inti of Measure: <th></th>	
Between 0.087 inches and 0.097 inches         First Diameter From Head:         Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No	
First Diameter From Head:   Between 0.100 inches and 0.104 inches   Distance From Largest Bearing Surface Of Head To End Of First Diameter:   0.252 inches   Internal Drive Style:   Cross recess type 1   Thread Diameter:   0.138 inches   Thready Qty Per Inch (tpi):   32   Externally Relieved Body Diameter Quantity:   1   Material:   Stainless steel   Surface Treatment:   Passivate   Thread Series Designator:   Unc   Shelf Life:   N'a   Diri Of Measure:   -   Demilitarization:   No	
Between 0.100 inches and 0.104 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.252 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         32         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:         Passivate         Thread Series Designator:         Unc         Sheff Life:         Na         Distore Treatment:         Na         Distore	
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.252 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Stainless steel Stainless steel Passivate Thread Series Designator: Unc Shelf Life: N/a Unic Of Measure: - Demilitarization: No	
0.252 inches Internal Drive Style: Cross recess type 1 Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Stainless steel Starface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.100 inches and 0.104 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 f Material: Stainless steel Striates steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: 	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Cross recess type 1 Thread Diameter: O.138 inches Thready Qty Per Inch (tpi): O2 Externally Relieved Body Diameter Quantity: I Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No	0.252 inches
Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):3232Externally Relieved Body Diameter Quantity:1Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:No	Internal Drive Style:
0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Cross recess type 1
Thready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:11Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:NaUnt Of Measure:Demilitarization:No	Thread Diameter:
32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No	0.138 inches
Externally Relieved Body Diameter Quantity:1Material:Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:No	Thready Qty Per Inch (tpi):
1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No	32
Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:No	Externally Relieved Body Diameter Quantity:
Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	1
Surface Treatment:   Passivate   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No	Material:
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Stainless steel
Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure:  Demilitarization:	Passivate
Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No	Unc
Unit Of Measure:  Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Demilitarization: No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A003b0	A003b0