NSN 5305-01-082-2198

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-082-2198

| Thread Class: |
|---------------------------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.346 inches and 0.438 inches |
| Fastener Length: |
| Between 0.408 inches and 0.438 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.370 inches and 0.380 inches |
| Head Height: |
| Between 0.132 inches and 0.142 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Screw Material: |
| Steel comp 8630 or steel comp 4037 |
| Screw Material Specification: |
| Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Special Features: |
| Head black federal standard 595, color no. 37038, furnished w/nylon washer |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |

NSN 5305-01-082-2198

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.