## NSN 5305-01-082-2746

Close Tolerance Screw - Page 1 of 2

3a

28

Material:

Passivate



View Online at https://aerobasegroup.com/nsn/5305-01-082-2746 **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.291 inches and 0.341 inches Fastener Length: Between 0.989 inches and 1.019 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response Surface Treatment: Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator: Specification Data:** 

80205-nas1154 professional/industrial association standard

Shelf Life:

N/a

Unjf



## NSN 5305-01-082-2746

Close Tolerance Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0