NSN 5305-01-082-3532



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-082-3532 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.344 inches and 0.375 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.308 inches and 0.332 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel **Screw Material Specification:** Qq-s-763, comp 410 federal specification single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-s-5002 military standard single treatment response **Test Data Document:** 81349-mil-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Mil-std (military Standard):

Mil-s-5002 spec.

No Fiig: A500d0