NSN 5305-01-082-4618

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-082-4618 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.370 inches **Fastener Length:** 0.660 inches **Head Style:** Hexagon **Head Height:** 0.180 inches Width Between Flats: 0.312 inches **First Diameter From Head:** 0.154 inches **Second Diameter From Head:** 0.104 inches **Third Diameter From Head:** 0.154 inches **Fourth Diameter From Head:** 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.138 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.167 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.181 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.290 inches **Internal Drive Style:** Torque **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4

Material:

Steel comp 303

Material Specification:

Qq-s-764 federal specification single material response

NSN 5305-01-082-4618

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 4 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0