NSN 5305-01-082-7063

Thread Class:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-082-7063

Thread Direction:
Right-hand
Thread Length:
Between 0.827 inches and 0.920 inches
Fastener Length:
Between 0.969 inches and 1.000 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.322 inches and 0.385 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-082-7063

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0