NSN 5305-01-082-8236

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-082-8236 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.466 inches and 0.597 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.452 inches and 0.507 inches **Locking Feature:** Patch threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response or mil-c-81562 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-082-8236

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.