NSN 5305-01-083-4078



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-083-4078 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.451 inches and 0.532 inches **Fastener Length:** Between 0.501 inches and 0.532 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 75000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303 or steel comp 303se **Screw Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a582 assn standard 4th material response or astm a582 assn standard 5th material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0