## NSN 5305-01-083-4662

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-083-4662 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Head Style:** Oval countersunk **Head Diameter:** 0.370 inches Point Length: 0.164 inches First Diameter From Head: 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.500 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 82.0 degrees **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 60.0 degrees Material: Steel comp 303 **Material Specification:** Qq-s-764, condition a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-e300 military specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

## NSN 5305-01-083-4662

Externally Relieved Body Screw - Page 2 of 2



	- : -	~	NA	
UI	nit	UΤ	Measure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072-e300 spec.