NSN 5305-01-084-2486

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-084-2486

2a Thread Direction: Right-hand Thread Length: 0.250 inches Fastener Length: 0.562 inches Head Style: Pan Between 0.473 inches and 0.492 inches Head Piameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thready Gty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment Specification: Gap-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-std-std-std-std-std-std-std-std-st	
Thread Direction: Right-hand Thread Length: 0.250 inches Fastener Length: 0.562 inches Head Style: Pan Between 0.473 inches and 0.492 inches Head Pight: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Ihernal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thread Style Per Inch (tpi): 20 Min Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Strew Material: Stainless steel Screw Material: Passivate Qap-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-std-std-std-std-std-std-std-std-st	Thread Class:
Right-handRight-handCasbi inchesCasbi inchesFastener Length:0.562 inchesHead Style:PanBetaden Jameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesInteral Drive Style:Cross recess type 1Thread Diameter:0.250 inchesDamoter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):80000 pounds per square inchCriticality Code Justification:FeatStrew Material:Stainless steelScrew Surface Treatment:PassivateArg-p-35 federal specification single treatment responseSpecial Features:IncHead Specification:InceStell Features:InceStell Features:Ince <td< th=""><th>2a</th></td<>	2a
Inread Length:0.250 inchesFastener Length:0.562 inchesHead Style:PanHead Diameter:0.492 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThread Diameter:0.250 inchesThread Piepter:0.250 inchesCriticality Code Justification:PareStanless stelScrew Material:Stainless stelScrew Surface Treatment:PasivateQuep-35 federal specification single treatment responseSpecial Features:Head painted lusterless olive drab color no. 34087 in accordance with fed-std-std-std-std-std-std-std-std-std-st	Thread Direction:
0.250 inches Fastener Length: 0.562 inches Head Style: Pan Head Diameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thread Diameter: 0.250 inches Thready Oty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Parewsurface Treatment Specification Pasivate Qa:p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-5td-5td-5td-5td-5td-5td-5td-5td-5td-5	Right-hand
Fastener Length:0.562 inchesHead Style:PanHead Diameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):80000 pounds per square inchCriticality Code Justification:FeatScrew Material:Stainless steelScrew Surface Treatment:PasivateQuep-3s federal specification single treatment responseSpecial Features:IncaHead painted lusterless olive drab color no. 34087 in accordance with fed-std-std-std-std-std-std-std-std-std-st	Thread Length:
0.562 inchesHead Style:PanHead Diameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThready Cty Per Inch (tpi):20Min. Tensile Strength (psi):80000 pounds per square inchCriticality Code Justification:FeatStrew Material:Stainless steelScrew Surface Treatment:PassivateQuep-35 federal specification single treatment responseSpecial Features:Inca Series Designator:UncStried Streis Designator:IncaStried Streis Designator:IncStried Streis Designator:IncStried Streis Designator:IncStried Streis Designator:IncStried Streis Designator:IncStried Life:NaInc Streis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncStreis Designator:IncInc Designator:Inc Designator:Inc Designator:<	0.250 inches
Head Style: Pan Head Diameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Qap-35 federal specification single treatment response Special Features: Head Specification: Unc Stries Designator: Via Unc Stries Designator: Via Unc Stries Designator: Via Dirt of Measure: N/a Dirt of Measure:	Fastener Length:
PanHead Diameter:Between 0.473 inches and 0.492 inchesHead Height:Between 0.162 inches and 0.175 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):80000 pounds per square inchCriticality Code Justification:FeatScrew Material:Stainless steelScrew Surface Treatment:PassivateQap-35 federal specification single treatment responseSpecial Features:Idad painted lusterless olive drab color no. 34087 in accordance with fed-std-std-std-std-std-std-std-std-std-st	0.562 inches
Head Diameter: Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Q-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Head Style:
Between 0.473 inches and 0.492 inches Head Height: Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Pan
Head Height: Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qap-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-5d95 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Head Diameter:
Between 0.162 inches and 0.175 inches Internal Drive Style: Cross recess type 1 Thread Diamete:: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qap-35 federal specification single treatment response Special Featurees: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-5td-5t8 Thread Series Designator: Unc Shelf Life: N/a Unit of Measure: - Demilitarization:	Between 0.473 inches and 0.492 inches
Internal Drive Style: Cross recess type 1 Cross recess type 1 Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Criticality Code Justification: Feat Screw Material: Stainless steel Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qap-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-505 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Head Height:
Cross recess type 1 Thread Diameter: O.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Acrew Surface Treatment Specification: Qu-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-5495 Thread Series Designator: Unc Shelf Life: N/a Inti Of Measure: Denilitarization:	Between 0.162 inches and 0.175 inches
Thread Diameter:0.250 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):80000 pounds per square inchCriticality Code Justification:FeatScrew Material:Stainless steelScrew Surface Treatment:PassivateScrew Surface Treatment Specification:Qu-p-35 federal specification single treatment responseSpecial Features:Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595Thread Series Designator:UncShelf Life:N/aUnit Of Measure:	Internal Drive Style:
0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Cross recess type 1
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-5095 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Thread Diameter:
20 Min. Tensile Strength (psi): 80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	0.250 inches
Min. Tensile Strength (psi):80000 pounds per square inchCriticality Code Justification:FeatScrew Material:Stainless steelScrew Surface Treatment:PassivateScrew Surface Treatment Specification:Qq-p-35 federal specification single treatment responseSpecial Features:Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595Thread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:	Thready Qty Per Inch (tpi):
80000 pounds per square inch Criticality Code Justification: Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	20
Criticality Code Justification: Feat Screw Material: Stainless steel Strew Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Min. Tensile Strength (psi):
Feat Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	80000 pounds per square inch
Screw Material: Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Criticality Code Justification:
Stainless steel Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Feat
Screw Surface Treatment: Passivate Passivate Crew Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Screw Material:
Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Stainless steel
Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Screw Surface Treatment:
Qq-p-35 federal specification single treatment response Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Passivate
Special Features: Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Screw Surface Treatment Specification:
Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Qq-p-35 federal specification single treatment response
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Special Features:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Head painted lusterless olive drab color no. 34087 in accordance with fed-std-595
Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization:	Unc
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
	-
	Demilitarization:
No	No
Fiig:	Fiig:
A500d0	A500d0