## NSN 5305-01-084-4677

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-084-4677 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.036 inches and 1.250 inches **Fastener Length:** Between 1.190 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.3750 inches and 0.3790 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 class 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-084-4677

Socket Head Cap Screw - Page 2 of 2



Uı	nit	Of	Measure:
----	-----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.