NSN 5305-01-084-4694



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-084-4694 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.306 inches and 0.356 inches **Fastener Length:** Between 0.878 inches and 0.908 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.2966 inches and 0.3016 inches **Shoulder Diameter:** 0.2021 inches first shoulder and 0.2026 inches first shoulder **Shoulder Length:** 0.512 inches first shoulder and 0.532 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Internal hexagon socket in threaded end 0.0791 in. Min and 0.0806 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-084-4694

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0