## NSN 5305-01-084-4708

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-084-4708 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.477 inches and 0.636 inches **Fastener Length:** Between 1.047 inches and 1.067 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.360 inches and 0.404 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Three 0.035 in. To 0.045 in. Wide splines in shank and 120 degrees Material: Steel comp 8740 or steel comp 4140 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-s-6049 spec.

Mil-std (military Standard):

A003b0