

View Online at <https://aerobasegroup.com/nsn/5305-01-084-5389>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.125 inches and 1.313 inches

Fastener Length:

Between 1.438 inches and 1.500 inches

Head Style:

Hexagon

Head Height:

0.281 inches

Width Between Flats:

0.625 inches

End Application:

Crane; tractor a/s32u-30; cargo truck, 5 ton

Thread Diameter:

0.438 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

14

Hardness Rating:

302.0 brinell standard and 352.0 brinell standard

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541

Material Specification:

Sae assn standard all material responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0