

View Online at <https://aerobasegroup.com/nsn/5305-01-084-5395>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.230 inches and 0.310 inches

Fastener Length:

Between 0.280 inches and 0.310 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy 260 or copper alloy 268 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 220 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 342

Screw Surface Treatment:

Silver

Screw Surface Treatment Specification:

Qq-n-290 grade c federal specification single treatment response and qq-s-365 grade a federal specification single treatment response

Precious Material And Location:

silver

Precious Material:

Silver

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0