

View Online at <https://aerobasegroup.com/nsn/5305-01-084-5395>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.230 inches and 0.310 inches

**Fastener Length:**

Between 0.280 inches and 0.310 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Screw Material:**

Copper alloy 260 or copper alloy 268 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 220 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 342

**Screw Surface Treatment:**

Silver

**Screw Surface Treatment Specification:**

Qq-n-290 grade c federal specification single treatment response and qq-s-365 grade a federal specification single treatment response

**Precious Material And Location:**

silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 9c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0