## NSN 5305-01-084-5409

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-084-5409

violi Cimilo di Inipeli/aci essacegi capicoli miloli mecco ci i co i c
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.380 inches and 0.447 inches
Fastener Length:
Between 0.640 inches and 0.687 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.338 inches and 0.381 inches
Head Height:
Between 0.039 inches and 0.041 inches
Shoulder Diameter:
0.202 inches first shoulder and 0.203 inches first shoulder
Shoulder Length:
0.240 inches first shoulder and 0.260 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Special Features:
Furnished with one o-ring
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5305-01-084-5409

Shoulder Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0